

# Interface® | Straightforward

## SPECIFICATION

<b>Product definition</b>	Microtuft Patterned Level Loop Tile	<b>Style number</b>	<b>3081230005</b>
<b>Pile Material</b>	100% BCF Solution Dyed Nylon contains pre-consumer recycled content	<b>Wear Classification</b>	EN 1307 33 Heavy Contract
<b>Pile Yarn Weight</b>	400g/m <sup>2</sup> ± 5%	<b>Radiant panel</b>	(EN ISO 9239/1) CfI S1 (EN ISO 13501)
<b>Total Weight</b>	4179g/m <sup>2</sup> ± 5%	<b>Hot Metal Nut</b>	Pass, low radius of effects of ignition (BS 4790)
<b>Pile Height</b>		<b>Castor Chair Rating</b>	≥ 2.4 (EN 985)
<b>Total Thickness</b>	4.8 mm ± 0.5 mm	<b>Dimensional Stability</b>	≤ 0.2% (ISO 2551 / EN 986)
<b>Gauge/Ends per 10cm</b>	5/64 - 50.4	<b>Vertical Electrical Resistance</b>	5 x 10 <sup>5</sup> Ω >> 1 x 10 <sup>9</sup> Ω Computerguard (ISO 10965) (IBM)
<b>Tufts per m<sup>2</sup></b>	176,400 ± 5%	<b>Colour Fastness - Light</b>	7 (ISO 105/B02)
<b>Backing Type</b>	Graphlex®	<b>Tiles per Box</b>	20 - 5m <sup>2</sup> (50 x 50 cm ± 0.15%)

06  
0336-CPD-8538

EN 1307

Non-Directional



**Mission Zero:**  
our promise to eliminate  
any negative impact our company  
may have on the environment  
by the year 2020.

[www.interface.com](http://www.interface.com)

Interface Europe Ltd reserve the right to change or modify specifications